


Tel: +86-755-32925789 ,Email: sales@linsnled.com , Website: www.linsnled.com  
 Address: Building 11, Sanlian Industrial Park, Shiyuan Town, Bao'an District, Shenzhen, China.

**P10.4-10.4 Transparent LED Display Specification**

**Tech Specification**

**LED Lamp**

No.	Items	Brightness	View Angle (Horizontal/Vertical)	Wave Length	Test Condition
1		Red LED	450~800mcd	120°±5°	25°C, 20mA
2		Green LED	750~1350 mcd	120°±5°	25°C, 18mA
3		Blue LED	130~220 mcd	120°±5°	25°C, 13mA

**LED Chip**

No.	LED Component	Model
1	SMD	SMD3512(Anti-UV)

**Details**

1	Pixel	10.4-10.4mm
2	Drive Mode	3 Scan
3	Module Resolution	48*24dots
4	Module Pixel	1152dots
5	Module Size	500mm*250mm
6	Cabinet Size (Width × Height)	1000*500mm/ 1000*1000mm
7	Cabinet Resolution	96*48/96*96
8	Transmittance	≥85%
9	Module Quantity	4pcs/8pcs
10	Pixel Density	9216 dots/m <sup>2</sup>
11	Material	Aluminium Profile
12	Cabinet Weight	8KG/16KG
13	Brightness	≥5000cd/m <sup>2</sup>
14	View Angle	Horizontal 140°, Vertical 140°
15	Minimum Viewing Distance	≥10m
16	Grey Level	16bit
17	Refresh Rate	≥1920HZ
18	Repetition Frequency	60fps
19	Input Voltage	AC 86-264V/60Hz
20	Power Consumption (Max/Average)	1000/330W/m <sup>2</sup>
21	Cabinet Weight	18kg/m <sup>2</sup>
22	Mean Free Error Time	>10,000 H
23	Lifetime	≥100,000 H
24	IP Protection Level	IP43
25	Temperature	- 20°C ~ +60°C or - 40°C ~ +60°C
26	Humidity	10%-85%RH
27	Control System	Novastar

