


Tel: +86-755-32925789 ,Email: sales@linsnled.com , Website: www.linsnled.com
 Address: Building 11,Sanlian Industrial Park, Shiyan Town, Bao'an District, Shenzhen, China.

P3.9 Transparent LED Display Specification

Tech Specification

LED Lamp

No.	Items	Brightness	View Angle (Horizontal/Vertical)	Wave Length	Test Condition
1		Red LED	450~800mcd	120°±5°	25℃,20mA
2		Green LED	750~1350 mcd	120°±5°	25℃,20mA
3		Blue LED	130~220 mcd	120°±5°	460-475nm

LED Chip

No.	LED Component	Model
1	SMD	SMD3512(Anti-UV)

Details

1	Pixel	3.96-7.81mm
2	Drive Mode	7 Scan
3	Module Resolution	500*250mm
4	Module Pixel	126*32dots
5	Module Size	4032dots
6	Cabinet Szie (Width × Height)	1000*500mm
7	Cabinet Resolution	252*64dots
8	Transmittance	≥68%
9	Module Quantity	4pcs
10	Pixel Density	32256 dots/m²
11	Material	Aluminium Profile
12	Cabinet Weight	11KG
13	Brightness	5500cd/m²
14	View Angle	Horizontal 140°, Vertical 140°
15	Minimum Viewing Distance	≥4m
16	Grey Level	16bit
17	Refresh Rate	>3840HZ
18	Repetition Frequency	60fps
19	Input Voltage	AC180-240V/60Hz
20	Power Consumption (Max/Average)	750/260W/m²
21	Cabinet Weight	13.5kg/m²
22	Mean Free Error Time	>10,000 H
23	Lifetime	≥100,000 H
24	IP Protection Level	IP30
25	Temperature	- 20℃~+60℃ or - 40℃~+60℃
26	Humidity	10%-85%RH
27	Control System	Novastar/ Linsn

